



Drying and sterilization ovens "Dry-Big"

FAN ASSISTED CIRCULATION.
 DIGITAL CONTROL AND DISPLAY OF TEMPERATURE AND TIME
 ADJUSTABLE TEMPERATURES FROM 40 °C UP TO 250 °C
 STABILITY: ± 0.4 °C, UP TO 100 °C. HOMOGENEITY: ± 2 °C, UP TO 100 °C
 SET ERROR : $\pm 2.5\%$ OF THE WORKING TEMPERATURE. RESOLUTION: 1 °C




SAFETY:

STANDARD EN.61010. FIXED OVER TEMPERATURE DEVICE FITTED.
 STANDARD DIN 12880. (CLASS 2 AND 3.1)ADJUSTABLE SAFETY THERMOSTAT FITTED.

Fast working and recovery temperature

FEATURES

1. Microprocessor controlled with digital display of temperature and time, pre-programmable time start and run time once the set temperature has been achieved through the Pt100 temperature sensor.
2. Inner chamber made of AISI 304 stainless steel.
3. Pre mixing chamber made of AISI 304 stainless steel.
4. Shielded heating elements with complete air circulation, homogeneously distributed throughout.
5. Low external temperature due to excellent thermal insulation.
6. Ventilation fan to force the air to circulate in the oven.
7. Diagram showing the air flow from the premixing chamber round the heating elements to the oven chamber.
8. Independent insulated control box.
9. Air inlet.
10. Ventilator with adjustable outlet of 120 Ø mm.
11. Shelf guides.
12. Shelves made of AISI304 stainless steel.
13. Flexible silicon door gasket around the entrance of the chamber.
14. Epoxy coated outer case.



Oven's diagram seen from the front side.

CONTROL PANEL

1. Illuminated mains switch.
2. Temperature mode indicator.
3. Time mode indicator.
4. Display for temperature and time.
5. Operating, Status mode.
6. Delay time state indicator.
7. Push button temperature selector.
8. Push button time selector.
9. Push button "increase" value or parameter.
10. Push button "decrease" value or parameter.
11. Push button Stop/Start.
12. Set temperature.
13. Set run time: time period from 1 minute to 9 hours 59 minutes, or up to 99.9 hours, once the set temperature value has been reached.
14. Set wait time before starting the run, time period from: 1 to 24 hours.
15. RS-232 Interface output to a computer or for printer.
16. Adjustable safety thermostat that overrides the microprocessor in case of failure, with manual reset and indicator lamp.





216 litres model. Part No. 2002961



720 litres model. Part No. 2003741



Part No. 2003743

STANDARD EQUIPMENT

2 Shelves.


MODELS

Part No.	Voltage	Capacity litres	Heating rate to reach 100 °C, minutes	Recovery time* minutes	Air exchanges per hour	Height / Width / Depth (interior) cm	Height / Width / Depth (exterior) cm	Number of shelf positions	Power W	Weight Kg
2002961	230 / 400									
	three phase	216	16	10	12	60 60 60	87 112 84	6	4000	150
2002962	230 single phase									
2002971	230 / 400									
	three phase	288	18	10	11	80 60 60	107 112 84	8	5000	161
2002972	230 single phase									
DOUBLE DOOR CABINET										
2003721	230 / 400									
	three phase	400	18	13	6	100 80 50	128 132 74	10	5250	200
2003741	230 / 400									
	three phase	720	19	13	6	120 100 60	150 152 80	12	6000	264
2003743	380 / 400									
	three phase	4200	30	13	6	180 175 135	216 231 178	10	11000	1200

Energy saving, three phase units are recommended.

*Recovery time, the door was opened for 60 seconds, time taken to recover to the set temperature of 100 °C.

Upon request, large capacity equipment can be manufactured.



Performance graph of temperature and time.


- A. Set at 250 °C: 1 h 6'.
- B. Set at 180 °C: 42'.
- C. Set at 100 °C: 24'.

ACCESSORIES

4.3 inches TFT touch screen. Must be installed in the factory.

Information and features. See page 139.

Part No. **2000010**



SPARES

Shelves.

Oven Part No. 2002961/62 2002971/72 2003721 2003741

Shelves **2000062** **2000062** **2000063** **2000064**