



## Drying and sterilization ovens "Digitheat-TFT"

NATURAL CONVECTION.  
 MICROPROCESSOR CONTROL WITH TFT TOUCH SCREEN.  
 ADJUSTABLE TEMPERATURE FROM AMBIENT +5 °C UP TO 250 °C.  
 STABILITY:  $\pm 0.3$  °C, UP TO 150 °C. HOMOGENEITY:  $\pm 1$  °C, UP TO 150 °C.  
 SET ERROR:  $\pm 2$  % OF THE WORKING TEMPERATURE. RESOLUTION: 1 °C.

PREMIER  
SERIE



NEW  
DESIGN

### SAFETY:

STANDARD EN.61010. INCORPORATED FIXED OVER TEMPERATURE DEVICE .  
 STANDARD DIN 12880. (CLASE 2 AND 3.1)CONTROLLABLE SAFETY THERMOSTAT FITTED.

## Reaches working temperature with minimum delay

FEATURES, CONTROL PANEL, SAFETY, STANDARD AND ACCESSORIES (see pages 138 and 139).



Model Digitheat type Poupinel,  
Part No. 2001253 and 2001255.




Model Digitheat, Part No. 2001251, 2001252 and 2001254.

### STANDARD EQUIPMENT

2 shelves and 4 shelf guides.

### MODELS

Part No.	Capacity litres	Height / Width / Depth (interior) cm			Height / Width / Depth (exterior) cm			Shelf Positions	Power W	Weight Kg
2001251	19	30	25	25	50	60	44	5	600	24
2001252	36	40	30	30	60	65	49	7	900	35
2001253	52	33	47	33	53	82	52	5	1000	44
2001254	80	50	40	40	70	74	59	8	1200	59
2001255	150	50	60	50	70	95	68	8	2100	73



Performance graph of temperature and time.

A. Set at 250 °C: 60'.

B. Set at 180 °C: 54'.

C. Set at 100 °C: 48'.

### SPARES

Shelves and guides.

Oven Part No.	2001251	2001252	2001253	2001254	2001255
Guides set (2 units)	2000011	2000012	2000012	2000013	2000015
Shelves	2000021	2000022	2000024	2000023	2000025

Each shelf requires two guides (one set).