

**TECHNICAL SPECIFICATIONS**

Trade name	Non-return valve
Use	Prevents water back-flow when pressure falls
Material	Polypropylene PP
Use range (temp. 20° C.)	0,07 - 2,00 BAR

**DIMENSIONAL SPECIFICATIONS**

External, diameter	mm. 12,00 - 13,00 - 15,00
Valley, diameter	mm. 9,50 - 12,50
Tapered conical tubes, diameter	mm. 9,50 - 12,50
General dimensional tolerance	mm. +/- 0,2
Weight	gr. 8,00 +/- 3%

**GENERAL FEATURES**

CE mark	No
Autoclavability	Yes
Sterilization	To be effected by radiations
Food contact suitable	Yes

**CHEMICAL RESISTANCE**

Categories of substances	Reference	Concen. %	T. 20°	T. 40°	T.° 60
Inorganic acid	Sulphuric acid	98	B	C	-
Organic acid	Benzoic acid	100	A	B	B
Alcohol	Ethanol	100	A	A	A
Aldehydes	Acetaldehyde	100	B	C	-
Inorganic alkali	Sodium hydroxide	50	A	A	A
Organic alkali	Aniline	100	A	B	C
Ketone	Acetone	100	A	A	-
Esther	Ethyl acetate	100	B	B	C
Hydrocarbons, halogenated	Dichloroethylene	100	C	-	-
Hydrocarbons, aromatic	Benzene	100	B	C	-
Hydrocarbons, linear	Hexane	100	B	B	C
Supersolvent	Tetrahydrofuran	100	B	B	C

**Legenda** (not applicable if neglected):

- **A: fair resistance**; exposure (30 days) to the chemical does not cause any damage.
- **B: sufficient resistance**; exposure causes damage of poor importance, which sometimes is only temporary.
- **C: poor resistance**; exposure to chemical is not allowed, or causes immediate permanent damage.

Results of testing with reference materials are to be considered as indication: in case of specific use it is recommended to carry out preliminary testing..

**PACKAGING**

Box	Pcs. 10
Case	Pcs. 3000

**Quality Assurance**

Massimiliano Capitanio

**Technical Direction**

Guido Borona