



Volumetric flasks, PMP, Class B with NS stoppers, PP



Highly transparent.

With ring mark individually calibrated to 'In'.

Class B tolerances according to DIN EN ISO 1042.

Thermal stress up to 121 °C (autoclaving) does not permanently exceed the tolerance limit.

To preserve markings, cleaning at no higher than 60 °C is recommended.

Volume ml	Tolerance ± ml	Height* mm	Neck NS	PU	Cat. No.
10	0.08	90	10/19	2	67795
25	0.08	115	10/19	2	67195
50	0.12	150	12/21	2	67295
100	0.20	180	14/23	2	67395
250	0.30	235	19/26	2	67495
500	0.50	270	19/26	2	67595
1000	0.80	310	24/29	1	67695

* Height without stopper



Volumetric flasks, PMP, Class B with screw caps, PP



Highly transparent.

With ring mark individually calibrated to 'In'.

Class B tolerances according to DIN EN ISO 1042.

Thermal stress up to 121 °C (autoclaving) does not permanently exceed the tolerance limit.

To preserve markings, cleaning at no higher than 60 °C is recommended.

Volume ml	Tolerance ± ml	Height* mm	Thread GL	PU	Cat. No.
10	0.08	90	18	2	677895
25	0.08	115	18	2	671895
50	0.12	150	18	2	672895
100	0.20	180	18	2	673895
250	0.30	235	25	2	674895
500	0.50	270	25	2	675895
1000	0.80	310	32	1	676895

* Height without screw cap