




PRODUCT SPECIFICATIONS SHEET

Combustion boat

Jizerská porcelánka s.r.o. certifies that the specified products meet all specifications and quality criteria for release. The products comply in every respect with the relevant particular specifications, drawings, relevant standards and regulations in force.

Sign	a (mm)	b (mm)	H (mm)	Approx. V (ml)
214/0 without eyelet	42	11	11	1
214/2	75	13	8	1,5
214/3	105	14	9	3
214/4	85	13	8	2,5
214/8	90	13	8	3
214/9	40	12	10	1
214/10	100	12	10	4
214/11	130	20	13	9
214/12	86	12	8	2,5





JIZERSKÁ PORCELÁNKA, s.r.o.

Producer of laboratory and technical porcelainsince1947



PRODUCT SPECIFICATIONS SHEET

Combustion boat

Intended uses: Laboratory applications

Material: Porcelain C110

Compliant to: ISO material for the manufacture lies within the group C110 according to ČSN EN 60672 –3
Product dimension tolerances are controlled by DIN 40 680
Acid resistance acc. to ISO 1775

Properties: Unglazed products can be used at temperatures of up to 1350°C / 2462°F and glazed ones at temperatures of up to 1000°C / 1,832°F (Δt 230°C)
Products have high resistance to acids and bases
Density 2.4 g/cm³
Dending strength of unglazed products (70MPa)
Thermal conductivity (W.m-1.K-1) = 1.3

The compliance of demands is proved by regular tests and followed noticed tests from an independent laboratory:

Test according ČSN EN 60672-2

Test resistance to acids and bases

Complies with Council Directive 84/500 EEC

Complies with Regulation No. 1935/201 of the European Parliament and of the Council

Disclaimer: *Jizerská porcelánka s.r.o. wants to state that these specifications can only be regarded as general information and will not discharge the user from his obligation to ensure the product is suitable for the intended use. If there's any doubt ask us.*