



## Water and oil baths "Precisterm"

ADJUSTABLE TEMPERATURE RANGE FROM AMBIENT +5 °C UP TO 110 °C, STABILITY  $\pm 1$  °C.  
ADJUSTABLE TEMPERATURE RANGE FROM AMBIENT +5 °C UP TO 200 °C, STABILITY  $\pm 2$  °C.

*Extensive range of sizes and accessories*

*Stainless steel interior and external case*



### FEATURES

Capacity; from 2 litres up to 45 litres.  
Double skinned tank of AISI 304 stainless steel with an exterior case of AISI 304 stainless steel.  
Heating elements embedded in INCOLOY heat and corrosion resistant stainless steel.

### CONTROL PANEL

Illuminated mains power switch.  
Hydraulic thermostat temperature control, synchronised with the "ON" indicator lamp.  
Safety thermostat cut out indicator lamp.

### MODELS

Part No.	Maximum Temperature °C	Capacity litres	Height / Widht / Fondo (usable) cm			Height / Widht / Depth (exterior) cm			Power W	Weight Kg
6000137	110	2	15	15	13	20	20	27	390	3.5
6000385	200	2	15	15	13	20	20	27	640	3.5
6000138	110	5	15	30	14	20	37	27	600	6
6000386	200	5	15	30	14	20	37	27	1110	6
6000140	110	12	15	30	30	20	40	42	1100	8
6000387	200	12	15	30	30	20	40	42	1400	8
6000141	110	20	15	48	30	20	58	42	1500	10
6000388	200	20	15	48	30	20	58	42	2100	10
6000142*	110	45	15	62	50	22	69	62	2400	18
6000389*	200	45	15	62	50	22	69	62	3800	18

All water baths are supplied with heating elements protection shelf.

\* With built in drain tap.

### SAFETY:

**DIN 12877 STANDARD.**  
**THE UNIT WILL CUT OUT IF THERE IS INSUFFICIENT LIQUID OR IF THE BATH TEMPERATURE EXCEEDS THE SET TEMPERATURE.**  
**A MANUAL RESET ADJUSTABLE TEMPERATURE SAFETY THERMOSTAT IS PLACED AT THE BACK OF THE UNIT.**



**ACCESSORIES.** See page 89.