

Laboratory Tech L-KG143HS / L-KG144HS

PRODUCT	DIMENSIONS	L-KG143HS	L-KG144HS
	Seat diameter	390 mm	390 mm
	Seat height	490-690 mm	590-840 mm

TECHNICAL DESCRIPTION

Seat	Structure in polyethylene anatomically shaped, 40 mm thickness, with integrated reinforcement ribs. Abrasion resistant, non-toxic and waterproof material, ideal for the food industry. Excellent resistance to corrosion and chemicals such as saline solutions, acids, alcohols and gasoline. It is not resistant to oxidizing acids such as nitric, sulfuric and halogens. Colours: Throna colour chart
Mechanism	GS: GAS LIFT, seat height adjustable.
Lift action	Central piston (Ø 28 mm) protected by steel tube (Ø 50 mm), black finish. Class 4 according to DIN 4550.
Base	0902P: 5-star base (Ø 600 mm) in nylon and fiberglass compound with internal reinforcement ribs, steel ring embedded in the conical coupling. Black finish. According to ANSI/BIFMA X5.1 and UNI EN 1335-3.
Glides	0351: glides in black nylon (h 55 mm / Ø 50 mm).

ACCESSORIES

M-0311	Soft castors (Ø 50 mm) in black nylon with non-marking polyurethane ring, self-braking. Instead of glides.
0700	Circular footrest (Ø 460 mm), chromed steel ring, supports in black painted steel, height adjustable with a knob.
M-0902C	5-star base (Ø 600 mm) in die-cast aluminum with internal reinforcement ribs. Polished finish.
M-0910V	5-star raised base (Ø 500 mm) in grey epoxy painted steel with rubber end-plugs.